

BUCKET & FAUCET FOUNTAIN



Supplies

- (1) 12" Plastic Carpet Saucer
- (1) Bag Polished Pebbles
- (1) Replacement Fountain Pump 70g
- (1) Galvanized Wash Tub, 4 gal
- (1) Brass Hosebarb 90°, 3/8" x 1/2"
- (1) Galvanized 90° Elbow, 1/2"
- (1) Galvanized Nipple, 1/2" x 5 1/2"
- (1) Brass Cooler Drain (342)
- (1) 1/2" outside x 3/8" inside Clear Vinyl Tubing
- (1) 1/2" MPT Hosebibb

Tools

Drill, 15/16" drill bit, 1/4": drill bit, adjustable wrench

Directions on reverse side.



2525 Arapahoe, Boulder, CO 80302
(303) 443-1822
mcguckin.com

BUCKET & FAUCET FOUNTAIN

Directions

1. Drill (1) 15/16" hole into Saucer 2½" from edge of saucer bottom.
2. Drill (20) ¼" holes randomly placed all over saucer bottom for drainage.
3. Attach Brass Cooler Drain to saucer through 15/16" hole. Washer side of Drain should end up on top side/ inside of saucer.
4. Attach 5½" Nipple to top of Drain.
5. Attach 90° Elbow to Nipple.
6. Attach Hosebibb to Elbow.
7. Attach Hosebarb to bottom of Drain.
8. Attach ½" Vinyl Tubing to Hosebarb.
9. Attach open end of Tubing to Fountain Pump.
10. Use Adjustable Crescent Wrench as needed to tighten joints.
11. Place Saucer/Fountain assembly level into Galvanized Bucket. Keep power cord of Fountain Pump free. Secure Pump to bottom of bucket.
12. Add enough water to cover Fountain Pump.
13. Plug in power cord, test fountain.
14. If successful water flow is made, add Polished Rocks to saucer to cover holes and bottom of saucer.